

## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2000-205458

(43) Date of publication of application: 25.07.2000

(51)Int.CI.

F16L 11/04

B32B 1/08

(21)Application number: 11-003596

(71)Applicant : TOKAI RUBBER IND LTD

(22)Date of filing:

11.01.1999 (72)Invent

(72)Inventor: FURUTA NORIHIKO


NIKI NOBUAKI IKEMOTO AYUMI


## (54) HOSE FOR CARBON DIOXIDE REFRIGERANT TRANSPORT

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a hose for transporting carbon dioxide refrigerant having multilayer structure in which a practical refrigerant permeability resistance is ensured while keeping flexibility, and which is avoided having a critical point in which refrigerant permeable amount is intensively changed to a enlarging diameter of a hose by providing a low permeable layer using a metal deposition layer between any of layers of the multilayer structure.

SOLUTION: A low permeable layer 6 made of metal deposition resin film is provided between an inner tube internal layer 1 and an inner tube external layer 3. The low permeable layer 6 is provided on an outer peripheral surface of an inter tube 7 constituted of a single layer. An inner tube is constituted of single layer or multilayer, each layer is made of rubber or resin. In the rubber layer, butyl rubber, chlorinated butyl rubber, brominated butyl rubber, acrylonitrile—butadiene rubber, chlorinated polyethylene rubber, ethylene propylene diene rubber,





chlorosulfonated polyethylene or the like is used. In the resin layer, it is preferable that a material which does not deteriorate flexibility of a hose such as polyamide resin or polyester resin is used, and the layer is lower than 150  $\mu$ m in thickness.

## **LEGAL STATUS**

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

BEST AVAILABLE COPY